

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Commissioner
US Department of Commerce
United States Patent and Trademark
Office, PCT
2011 South Clark Place Room
CP2/5C24
Arlington, VA 22202
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 18 January 2001 (18.01.01)	
International application No. PCT/US00/04765	Applicant's or agent's file reference
International filing date (day/month/year) 24 February 2000 (24.02.00)	Priority date (day/month/year) 24 February 1999 (24.02.99)
Applicant KITHIL, Philip, W.	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:22 September 2000 (22.09.00)☐ in a notice effecting later election filed with the International Bureau on:2. The election ☒ was☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	Authorized officer S. Mafia Telephone No.: (41-22) 338.83.38
--	---



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : B60R	A2	(11) International Publication Number: WO 00/50261 (43) International Publication Date: 31 August 2000 (31.08.00)
(21) International Application Number: PCT/US00/04765 (22) International Filing Date: 24 February 2000 (24.02.00) (30) Priority Data: 60/121,653 24 February 1999 (24.02.99) US 60/138,139 8 June 1999 (08.06.99) US (71) Applicant (for all designated States except US): ADVANCED SAFETY CONCEPTS, INC. [US/US]; Suite E-12, 1570 Pacheco Street, Santa Fe, NM 87505 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): KITHIL, Philip, W. [US/US]; 1274 Vallecito Drive, Santa Fe, NM 87501 (US). (74) Agent: MYERS, Jeffrey, D.; Peacock, Myers & Adams, P.O. Box 26927, Albuquerque, NM 87125-6927 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>Without international search report and to be republished upon receipt of that report.</i>
(54) Title: CAPACITIVE SENSORS FOR VEHICULAR ENVIRONMENTS		
(57) Abstract		
<p>Capacitive sensors used to detect force upon a transparency product for detecting and discriminating crash characteristics of a vehicle, as well as capacitive sensors used in conjunction with a conductive panel functioning as an airbag cover and ground plane for the capacitive sensors. The capacitive sensors are made up of electrodes, of which one may be a conductive coating. The capacitive sensors can be arranged upon a substrate and can include a reference sensor. Long term effects of temperature upon sensor output are compensated for with an algorithm comparing constant desired sensor output to low frequency drift due to temperature effects. Moisture upon a transparency product is distinguished from a nearby object due to the capacitance sensed. A sleep detection algorithm detects when a vehicle operator is drowsy. A capacitive sensor array having a nested circle sensor and L-shaped sensors, along with a dummy sensor is used in a sunroof-equipped vehicle for sensing occupant head position.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

-31-

CLAIMS

What is claimed is:

Add any

5 1. A force detecting capacitive sensor comprising at least two electrodes integral with a transparency product, and optionally wherein at least two of said at least two electrodes are parallel with one another, and optionally wherein at least two of said at least two electrodes are nonparallel with one another, and preferably wherein said transparency product is glass, and more preferably wherein said transparency product is a vehicle windshield.

10 2. The sensor of claim 1 wherein at least one of said at least two electrodes comprises a conductive coating integral with said transparency product.

15 3. A system for detecting force which imparts momentary bending to a transparency product, said system comprised of at least one force detecting capacitive sensor integral with a transparency product, preferably wherein said at least one sensor is configured for discriminating different vehicle crash characteristics, and preferably wherein said system further comprises a vehicle occupant protection system comprised of at least one occupant restraint device which operates in conjunction with said system for detecting force.

20 4. A system for detecting a visibility condition of a transparency product, said system comprising at least one capacitive sensor integral with the transparency product, and preferably wherein said system distinguishes between a visibility condition and an object in proximity to the transparency product, and preferably wherein said system operates in conjunction with a vehicle
25 occupant protection system to distinguish between a vehicle occupant in proximity to the transparency product and condensed moisture on the transparency product, and preferably wherein said system further initiates a response to modify the visibility condition.

-32-

5. A method of compensating for the long-term effects of temperature on a sensing system, the method comprising the steps of:

- a) determining the constant desired sensor output;
- b) determining low frequency shifts due to temperature effects;
- 5 c) comparing the constant desired sensor output to the low frequency shifts due to temperature effects; and
- d) employing a compensation algorithm to account for the difference.

6. A vehicle occupant detecting capacitive sensor in combination with a conductive panel functioning as a vehicle airbag door and ground plane for said capacitive sensor, and preferably further comprising additional capacitive sensors, all of said capacitive sensors fabricated on a substrate material adjacent said conductive panel, and preferably wherein said capacitive sensors are each assigned to at least one triangle for discriminating occupant proximity and providing data to an airbag controller, and preferably wherein said capacitive sensors are circular.

7. A method of configuring a capacitive sensor and a reference sensor on a dielectric substrate, the method comprising the steps of:

- a) fabricating a reference sensor and a capacitive sensor on a substrate;
- b) placing a monolithic ground on a reverse side of the substrate;
- 20 c) attaching a printed circuit board to a deleted portion of the monolithic ground;
- d) connecting the reference sensor to electronic parts on the printed circuit board; and
- e) compensating for changes in capacitive sensor output which are not related to proximity of a vehicle occupant by comparing the capacitive sensor output to the reference sensor output.

8. A method of detecting head motion indications of a drowsy vehicle operator, the method comprising the steps of:

- a) representing the drowsy vehicle operator's head motion with a four-dimensional feature vector;
- 5 b) training a feature detection network;
- c) utilizing a sleep detector to detect head motion that does not look like an alert operator's head motion and does look like a feature associated with a sleep nod;
- d) customizing the sleep detector for individual vehicle operators; and
- e) identifying the operator of a vehicle and modifying sleep detector parameters
- 10 based on historical data attributable to the identified operator.

9. A capacitive occupant sensing system for a sunroof-equipped vehicle to monitor an occupant's head position, said system comprising a nested circle capacitive sensor, and at least one L-shaped capacitive sensor adjacent said nested circle capacitive sensor, wherein said nested circle capacitive sensor and said at least one L-shaped capacitive sensor are located adjacent the sunroof, and optionally further comprising a dummy sensor located on the opposite side of the sunroof from said nested circle capacitive sensor and said at least one L-shaped capacitive sensor.

15

10. A method of sensing an occupant's head position in a sunroof-equipped vehicle with a dummy sensor and a nested circle capacitive sensor array, the method comprising the steps of:

20

- a) positioning a dummy sensor on an opposite side of the sunroof from the nested circle capacitive sensor array adjacent the sunroof;
 - b) deriving a composite head position from the dummy sensor head position and the triangulated head position from the nested circle capacitive sensor array;
 - 25 c) identifying the operator by comparing the head coordinates of the operator to historical data attributable to the identified operator; and
 - d) updating parameters which identify non-impairment conditions of the operator.
- 30